

PRODUCTS CATALOGUE

"AT EASE IN YOUR CONSTRUCTION SITE"

www.ritmo.it





Ritmo meets all your welding needs in your jobsite



The information and photos in this publication are not binding and RITMO S.P.A. is free to make any alterations without prior notice.

A DVANTAGE

RITMO



RITMO WORLDWIDE

Ritmo has professional distributors and resellers all over the world. Our staff is ready to assist you in English, Spanish, French, German, Arab, Italian, Russian and Portuguese.

TRAINING

From many years now, we have decided that the best way to grant a client/distributor a perfect knowledge of our products is to invest in custom training, in our own premises. These courses are aimed to teach how to operate the products in the best way, and how to supply the "first aid" when necessary.

PRESALES TECHNICAL ASSISTANCE

When a client or a potential client wants to buy us a product, it is our standard procedure to help find the best solution to its needs.

GLOBAL ADVICE

In such a technical field as ours, the customer requires the best assistance. Thanks to the experience developed along the years, and to the co-operation with several manufacturers, institutions, schools and training institutes, RITMO is able to give the most comprehensive advice to no matter which related issue. Our company is a long-time member of a UNIPLAST's (UNI-Italian National Plastics Standards Body) working group dedicated to the study and draw up of new standards within our field. The importance of this group is linked to the fact that the expansion of the plastic welding field ought to be followed by a crescent sensitivity for safety issues, so to have a sustainable and continuous growth. The working group prepares draws, hence present them to the UNI to be discussed and eventually transformed into new standards.

AFTER SALES TECHNICAL ASSISTANCE

Ritmo's Service Centre can solve all kind of technical issues, as well as overhaul our machines. Ritmo has other Service Centres abroad, linked to its official distributors.

STARTING AND TESTING

RITMO' technicians are prepared to make the starting and testing of workshop machines at the client' own premises, so that the fittings production can start almost immediately.

RITMO'S BUTT FUSION MACHINES: WORK PHILOSOPHY AVAILABLE TO EVERYONE!

- **MANUAL**

welding machines without hydraulic gearcase



- **HYDRAULIC**

welding machines with hydraulic gearcase



- **EASY LIFE SYSTEM** *HIGH LEVEL PERFORMANCE*

automated welding cycle


welding machines with special hydraulic gearcase

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF,

APP "SET & GO PRO" (optional)



- **ALL TERRAIN/REMEDY** *HIGH LEVEL PERFORMANCE*

self-contained generator on board

self-propelled

trolley with wheels

welding machines with special hydraulic gearcase

automated welding cycle

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF,



- **CNC** *HIGH LEVEL PERFORMANCE*

automatic welding cycle

special hydraulic gearcase and machine body with

integrated mechanical extraction of heating plate

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF



ALL TERRAIN - TRAILER - REMEDY LINE ***HIGH LEVEL PERFORMANCE***



DIFFERENCES BETWEEN ALL TERRAIN, TRAILER AND REMEDY LINE

PLUS

**HIGH
PERFORMANCE**

**ENHANCES
PRODUCTIVITY**

	ALL TERRAIN	TRAILER	REMEDY
Working standards mm	✓	✓	✓
Working standards "IPS /"DIPS	✓	✓	✓
International standards ISO 21307 HIGH PRESSURE and ASTM F2620	✓	✓	✓
Welds fittings	✓	✓	✓
Easy Life Welding System	✓	✓	✓
Data-logging	✓	✓	✓
PRE-SET 20 customized welding cycles	✓	✓	✓
Intuitive control panel	✓	✓	✓
GPS traceability	✓	✓	✓
Report PDF	✓	✓	✓
Self-contained Generator on-board	✓	-	✓
Heater/Facer on-board	✓	✓	✓
Insert - Fast-locking system	✓	✓	✓
Trolley with wheels	✓	✓	-
Self-propelled on wheel	✓	-	-
Self-propelled on track	-	-	✓
Remote control track	-	-	✓
Remotely wire-controlled IN-DITCH USE up to 12 m (39 ft)	✓	✓	✓
Carriage can be removed for in-ditch use	✓	✓	✓
Lateral rollers	✓	✓	✓







DELTA 500 TRAILER

DELTA 500 TRAILER is a self-aligning fusion machine, suitable for welding thermoplastic pipes for the transport of water, gas and other fluids under pressure, up to Ø 500 mm (6" IPS ÷ 20" IPS). Machine can fuse pipes according to the ISO 21307 High Pressure standard and ASTM F2620. Standard machine features:

- Machine body mounted on a 4 wheeled chassis, easily removable for working in tight spaces.
- New RITMO Patented assisted system to open/close/lift clamps-heater-facer.
- Machine body with an automatic heating plate detaching device: helps removing the heating plate safely and fast
- Fast-locking system which allows to place and remove inserts in seconds.
- 4 wheeled chassis with 2 steering wheels and a safety brake .
- An on-board milling cutter that is equipped with a safety microswitch to prevent from accidental starts, a thermal circuit breaker to protect motor and also features an ergonomic docking system and on/off switches.
- An on-board heating plate Teflon-coated (PTFE) which comes with a high-temperature-proof bag, which also avoid the heating element from being scratched.
- Removable control panel with data-logging, memory up to 4000 welding reports, GPS traceability; USB port for welding PDF report / data download / firmware upgrade .
- Easy-life welding control system: hardware and software have been developed to interact to each other sharing data during the entire workflow. Once set the welding parameters up, the system guarantees the repetition of the welding cycles, avoiding errors. The operator only have to confirm the work phases on the just pushing a button. Possibility to pre-set 20 customized welding cycles.
- Two hydraulic rollers for pipe loading and unloading.

DELTA 500 TRAILER allows to easily weld fittings like elbows, tees, Y-branches and stub flanges. Available in 230 V single phase or three phase.

STANDARD COMPOSITION



Machine body



Hydraulic
Rollers




Trolley



Control panel
with GPS



Milling cutter



Heating plate

TECHNICAL FEATURES

PLUS

200 ÷ 500 mm

ISO 21307

HIGH PRESSURE

Assisted system
to open/close/lift
clamps-heater-facer

Working range	200 ÷ 500 mm; 6" IPS ÷ 20" IPS
Materials	HDPE, PP For other materials contact RITMO S.P.A.
Power supply	230 V Single Phase 50/60 Hz 230 V Three Phase 50/60 Hz
Total absorbed power*	7250 W
Working temperature	180° ÷ 280° C (356° ÷ 536° F)
Outside temperature range	-10° ÷ 40° C (14° ÷ 104° F)
Dimensions machine body (W x D x H)	1822 x 1152 x 814 mm 71.8" x 45.4" x 32"
Dimensions trolley (W x D x H)	3295 x 1385 x 1331 mm 130" x 53" x 52.4"
Weight machine body	580 Kg (1279 lb)
Weight Trolley	270 Kg (595.3 lb)
Weight standard composition	850 Kg (1830 lb)

* Suggested power generator
12kVA



ON REQUEST



Inserts
Ø 200 ÷ 500 mm



Tool for flange
necks



HS Rollers 630

and:
Inserts Ø 6" ÷ 18" IPS; 6" ÷ 18" DIPS; KIT for IN-DITCH USE

India



BUTT FUSION MACHINES REFERENCE



WORKING RANGE Ø mm	32	40	50	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	710	800	900	1000	1200	1400	1600		
GAMMA 160		40	50	63	75	90	110	125	140	160																					
DELTA 160 M	32	40	50	63	75	90	110	125	140	160																					
DELTA 200 M				63	75	90	110	125	140	160	180	200																			
BASIC 160		40	50	63	75	90	110	125	140	160																					
BASIC 200				63	75	90	110	125	140	160	180	200																			
BASIC 250					75	90	110	125	140	160	180	200	225	250																	
BASIC 315						90	110	125	140	160	180	200	225	250	280	315															
BASIC 355								125	140	160	180	200	225	250	280	315	355														
COMPACT 355								125	140	160	180	200	225	250	280	315	355														
BASIC 160 EASY LIFE		40	50	63	75	90	110	125	140	160																					
BASIC 200 EASY LIFE				63	75	90	110	125	140	160	180	200																			
BASIC 250 EASY LIFE					75	90	110	125	140	160	180	200	225	250																	
BASIC 315 EASY LIFE						90	110	125	140	160	180	200	225	250	280	315															
BASIC 355 EASY LIFE								125	140	160	180	200	225	250	280	315	355														
DELTA 500 EASY LIFE												200	225	250	280	315	355	400	450	500											
DELTA 630 EASY LIFE															280	315	355	400	450	500	560	630									
DELTA 500												200	225	250	280	315	355	400	450	500											
DELTA 630															280	315	355	400	450	500	560	630									
DELTA 800																				500	560	630	710	800							
DELTA 1000																						630	710	800	900	1000					
DELTA 1200																							710	800	900	1000	1200				
DELTA 1600 ECO / 1600 HDR																								800	900	1000	1200	1400	1600		
DELTA 250 TRAILER / MANUAL					75	90	110	125	140	160	180	200	225	250																	
DELTA 355 TRAILER DELTA 355 ALL TERRAIN								125	140	160	180	200	225	250	280	315	355														
DELTA 500 TRAILER DELTA 500 ALL TERRAIN												200	225	250	280	315	355	400	450	500											
REMEDY 500 FA														250	280	315	355	400	450	500											
DELTA 630 TRAILER DELTA 630 ALL TERRAIN													225	250	280	315	355	400	450	500	560	630									
DELTA 1000 TRAILER																315	355	400	450	500	560	630	710	800	900	1000					
REMEDY 1000 EL																315	355	400	450	500	560	630	710	800	900	1000					
DELTA DRAGON 250 CNC					75	90	110	125	140	160	180	200	225	250																	
DELTA DRAGON 315 CNC						90	110	125	140	160	180	200	225	250	280	315															
WORKING RANGE Ø mm	32	40	50	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	710	800	900	1000	1200	1400	1600		

RITMO S.p.A.
Via A. Volta, 35/37 - 35037
Bresseo di Teolo (PADOVA) ITALY

Ph. +39 049 9901888
Fax +39 049 9901993

info@ritmo.it
www.ritmo.it

